

MANUAL CPVC VSEP SYSTEM SPECIFICATIONS

Updated: 12/29/08

1] Filter Pack

Membrane:	NF 500/PS100
Maximum Operating Temperature:	160 °F (70°C) (Options for up to 130°C)
Allowable Feed Slurry pH Range:	2-11 (Options for 1-14)
O-ring Material:	EPDM (Options for Viton)
Filter Pack Housing:	Vinyl Ester 8084 Derekane Fiberglass
Wetted Steel Trays:	304 Stainless Steel .018 Gauge (Option for 316SS)
Wetted Plastic End Plates:	Polypropylene (Options for Teflon, Aluminum)

2] Piping

Maximum Pressure:	550 psi (Options for up to 1200 psi)
Pressure Piping:	316L Stainless Steel Schedule 80
Atmospheric Piping:	CPVC Schedule 80
Special VSEP Concentrate Pipe:	1-1/4" Alloy 20 Stainless Steel .065 wall
Flexible Hoses:	Neoprene Lined Reinforced Eastman Flex Hose
Pipe Clamps:	<i>Victaulic</i> Zero-Flex Style 07 EPDM
Manual Valves:	<i>Hayward</i> CPVC 3-Piece Ball Valves w/ Viton seats
Flow Control Valve:	<i>FloTite</i> V300 Series 316SS 60 degree V-Ball <i>BLX</i> V100E positioner
Ball Check Valves:	<i>Hayward</i> CPVC Ball Check Valve
Pneumatic Actuators:	None
Skid Piping Terminations:	150lb 1.5"/2" CPVC Flange EPDM
Pneumatic Air Supply:	90lb Instrument Grade Air (3/8"npt connection to FCV)
Clean in Place Tank:	260 Gallon Cross Linked Polypropylene w/ Lid (36" ø x 74")

3] Vibration System

Motor:	<i>Baldor</i> CM4106T 460VAC, 3phase, 20HP, 3525 RPM
Motor Speed Controller:	<i>AC Tech</i> 20HP NEMA 4 (or Equal)
Vibration Amplitude:	3/4 inch (peak to peak measured at the Filter Pack)
Frequency Range:	49.0 hz to 55.0 hz (Approximate)
Maximum Decibels:	<85
Bearing RPM:	2800 to 3100
Bearing Oil:	<i>Sullube</i> ~750 ml Compressor Oil
Bearing O-rings:	2-263 & 2-270 Buna

4] Electrical Specifications:

Controls Voltage:	220/120VAC, 1phase, 15A, 50/60Hz
Programmable Controller Type:	<i>Allen-Bradley</i> CompactLogix 1769
Touch Screen Display Type:	<i>Allen-Bradley</i> PanelView+ 1000
Enclosures:	<i>Hoffman</i> NEMA 4 Powdercoat Finish 48x30x10, 24x30x8
Switches, Relays, & Contactors:	<i>Allen Bradley</i> 220/110 Volt
Pressure Sensors:	<i>Efector</i> PN-2222
Flow Meters:	<i>Yamatake</i> MGG18D-050P21CS5ACA-XX
Flow Transmitters:	<i>Yamatake</i> MGG14C-MH4G-1A1N-YAH
Temperature Indicator:	<i>Ashcroft</i> Dial Gauge 0-150 degF

5] Pump Specifications:

Feed Pump Type:	<i>Grundfos</i> 316SS 66gpm Vertical Multi-stage Centrifugal
Feed Pump Motor:	<i>Grundfos</i> ML 20 HP 3500 rpm TEFC 460VAC, 3phase, 30A
Motor Speed Controller:	<i>AC Tech</i> 20HP NEMA 4 (or Equal)

MANUAL CPVC VSEP SYSTEM SPECIFICATIONS

6] Pre-Screen Basket Strainer:

Filter Housing Type (or equal):	<i>NLR</i> Custom Made
Basket Strainer:	60 Mesh 316 SS
Capacity:	220 GPM
Filter Housing Material:	316L Stainless Steel
Elastomers (Seals):	EPDM, (Options for Buna, Viton - Depending on Process)

7] Operating Site Conditions:

Equipment Rating:	NEMA 4, Indoor/Outdoor protect from sunlight & rain.
Ambient Temperature:	5 - 37°C
Storage Temperature:	2 - 70°C (Protect Filter Pack from Freezing)
Max Relative Humidity:	<95%, non-condensing
Elevation:	3300 ft maximum without derating