

**MANUAL SPIRAL SYSTEM SPECIFICATIONS: (S-3200 Unit)**

Updated: 7/27/09

**1] Filter Pack**

<b>Membrane:</b>	LFC 3LD
<b>Membrane Surface Area:</b>	3600sf (340m <sup>2</sup> ) (9ea 8”Dia x 40”L)
<b>Estimated Production:</b>	12-24gpm (at 5-10GFD)
<b>Maximum Operating Temperature:</b>	120 °F (49°C) (Options for up to 80°C)
<b>Allowable Feed Slurry pH Range:</b>	2-11 (Options for 1-14)
<b>O-ring Material:</b>	Ethylene Propylene
<b>Filter Pack Housing:</b>	Polyurethane Coated, Filament Wound, Epoxy FRP
<b>Wetted Ports:</b>	316 Stainless Steel
<b>Wetted Plastic End Plates:</b>	PVC Thermoplastic

**2] Piping**

<b>Maximum Pressure:</b>	600 psi (4140 kPa) (Options for up to 1000psi)
<b>Pressure Piping:</b>	316 Stainless Steel Schedule 40
<b>Atmospheric Piping:</b>	CPVC Schedule 80
<b>Pipe Clamps:</b>	<i>Victaulic</i> Zero-Flex Style 07 EPDM
<b>Manual Valves:</b>	<i>Hayward</i> CPVC 3-Piece Ball Valves w/ Viton seats
<b>Manual Gate Valves:</b>	<i>JFW Valves GT-200</i> ASTM SW 1-Piece Valves w/ Teflon seats
<b>Ball Check Valves:</b>	<i>Hayward</i> CPVC Ball Check Valve
<b>Pneumatic Actuators:</b>	None
<b>Skid Piping Terminations:</b>	150lb 2”/1.5”/1” CPVC Flange EPDM
<b>Clean in Place Tank:</b>	20 Gallon Polypropylene w/ Base (19” ø x 28”)

**3] Electrical Specifications:**

<b>Programmable Controller Type:</b>	None (Start/Stop signal from VSEP PLC)
<b>Touch Screen Display Type:</b>	None
<b>Enclosures:</b>	<i>Hoffman</i> NEMA 4 Powdercoat Finish 24x20x8
<b>Transformer:</b>	<i>Square D</i> 208/230/460:115 150VA
<b>Power Supply:</b>	<i>IDEC</i> 24VDC 7.5W
<b>Start, Stop, HOA Switches:</b>	<i>Allen Bradley</i> 220/120VAC
<b>Relays, &amp; Fuses:</b>	<i>Potter Brumfield</i> 15A 24VDC
<b>Pressure Indicators:</b>	<i>Ashcroft</i> Dial Gauge 0-30psi, 0-600psi
<b>Flow Indicator:</b>	<i>GPI</i> Paddlewheel 4352k55
<b>Temperature Indicator:</b>	<i>Ashcroft</i> Dial Gauge 0-150 degF

**4] Pump Specifications:**

<b>Feed Pump Type:</b>	<i>Grundfos</i> 316SS 44gpm Vertical Multi-stage Centrifugal
<b>Feed Pump Motor:</b>	<i>Grundfos</i> 15 HP 3500 rpm TEFC 460VAC, 30A, 3 Phase 60Hz
<b>Motor Speed Controller:</b>	<i>AC Tech</i> 15HP NEMA 4 (or Equal)

**5] Pre-Screen Basket Strainer:**

<b>Filter Housing Type:</b>	<i>Keystone</i> Water Filter
<b>Filter Cartridge:</b>	Polyester 50micron
<b>Capacity:</b>	25 GPM
<b>Filter Housing Material:</b>	Clear Styrene
<b>Elastomers (Seals):</b>	EPDM



1295 67th St. Emeryville, CA 94608 510.655.7305 510.655.7307 fax www.vsep.com

**MANUAL SPIRAL SYSTEM SPECIFICATIONS: (S-3200 Unit)**

**6] Operating Site Conditions:**

<b>Equipment Rating:</b>	NEMA 4, Indoor/Outdoor protect from sunlight & rain.
<b>Ambient Temperature:</b>	5 - 37°C
<b>Storage Temperature:</b>	2 - 70°C (Protect Membranes from Freezing)
<b>Max Relative Humidity:</b>	<95%, non-condensing
<b>Elevation:</b>	3300 ft maximum without derating