VSEP Vibes Newsletter

Welcome to the New Logic Research Newsletter

The Environmental Catastrophe you Never Heard of, Ecuador's March 2025 Pipeline Rupture

On the evening of March 13, 2025, in Ecuador's Esmeraldas province, a catastrophe occurred. Weeks of intense precipitation destabilized slopes above the Trans-Ecuadorian Pipeline System (SOTE), Ecuador's primary crude transport artery. In the rural parish of Cube, a landslide sheared through the buried government owned and operated pipeline, releasing crude oil into a small stream that quickly fed into the Caple, Viche, and ultimately the Esmeraldas River. Within hours, what began as a localized rupture evolved into a watershed-scale contamination event. Witnesses described an uncontrolled release that gushed for hours before containment efforts began. The failure was not simply longitudinal rupture, but a high-energy discharge condition, indicating that isolation valves were either too remote, slow to actuate, or compromised by terrain access.

The spill was estimated at roughly 25,000 barrels, though early field reports suggested higher volumes. What is certain is the crude migrated more than 80 kilometers downstream, contaminating multiple tributaries and ultimately reaching sensitive coastal ecosystems. From an environmental systems perspective, the consequences were immediate and severe. The Caple and Viche Rivers turned anoxic, stripped of dissolved oxygen, triggering rapid fish kills and collapse of local aquatic systems. Mangrove channels at the Esmeraldas estuary, among the most productive and sensitive coastal biomes, became coated in hydrocarbons, impairing sediment chemistry and threatening long-term ecological function.

For nearby communities, the failure cascaded into a full-scale infrastructure crisis. The Esmeraldas River serves as a primary water source for hundreds of thousands of residents; contamination forced authorities to shut down municipal intakes and impose rationing. As many as 300,000 people lost access to

safe water, while reports of respiratory distress, dermal exposure, and gastrointestinal illness followed quickly. Containment presented its own challenges. Emergency earth berms and dikes were installed along the affected waterways, but continued rainfall destabilized these temporary controls, causing failures that allowed oil to remobilize. Access constraints in saturated terrain further slowed response efforts.

This incident is not isolated. Petroecuador has experienced multiple pipeline failures in recent years, most notably the 2020 rupture near the Coca River, where erosion undermined several major pipelines simultaneously. More broadly, the country has recorded hundreds to over a thousand oil spill events over the past two decades, reflecting systemic vulnerabilities in aging government owned infrastructure and its interaction with dynamic Andean and tropical landscapes.

The March 2025 Esmeraldas spill underscores a recurring engineering dilemma: linear infrastructure operating in nonlinear terrain. Landslides, river migration, and extreme weather are not anomalies here, they are design conditions. For pipeline operators, the failure is less about a single rupture point and more about network resilience. The lesson from Esmeraldas is clear, pipelines must be designed not just to move oil, but to coexist with the landscapes that increasingly reshape them. Full clean-up will take years or decades. New Logic has been contacted to provide a river water filtration system for 8000 m3/hr.

VSEP Vibes Newsletter

PFAS and the Beverage Industry: When Water Quality Becomes Product Liability

For decades, per- and polyfluoroalkyl substances, or PFAS, were used with little public scrutiny. What was not fully understood at the time is that PFAS do not break down in the environment. Instead, they persist, migrate, and accumulate. Today, they are detectable in soil, wildlife, crops, and, most critically in drinking water supplies. That persistence has begun to reshape the legal and commercial landscape for the beverage industry. This shift became particularly clear in 2023, when consumer lawsuits began targeting beverage brands whose products contained detectable PFAS, even when those products were made using municipally supplied drinking water. The legal argument was simple but powerful: consumers were not informed that "pure," "natural," or "healthy" beverages contained industrial chemicals associated with long-term health risks.

One of the most widely cited examples involves mineral and sparkling waters. After independent testing and media reporting found PFAS in Topo Chico natural mineral water, class-action lawsuits were filed against Coca-Cola, which acquired the brand in 2017. The cases alleged that the presence of PFAS conflicted with the product's marketing and that consumers would have made different purchasing decisions had they known. Coca-Cola ultimately agreed to a settlement and committed to investing in additional filtration, while stating that it did not admit wrongdoing. Nevertheless, the case became a watershed moment for the industry, signaling that reliance on source water quality alone was no longer a sufficient defense.

Other beverage categories soon followed. Lawsuits alleging undisclosed PFAS have been filed against producers of juices, bottled waters, and sports drinks, including widely publicized claims involving newer hydration brands. In several cases, plaintiffs have pointed to the use of municipal water supplies

known to contain low, but detectable, levels of PFAS. Even when concentrations fell below proposed regulatory limits, the central issue was non-disclosure. Courts have shown increasing willingness to allow these cases to proceed under consumer protection and false advertising statutes, particularly when products were positioned as wholesome or health-forward.

Sparkling waters tell a similar story. Several high-profile brands have tested positive for PFAS at varying levels. In each instance, the contamination was traced back to the source—often spring water that had not undergone advanced treatment. The long-standing consumer perception that spring water is inherently cleaner than purified water is being challenged by the chemistry. Reverse osmosis–treated water, once criticized as overly processed, is now recognized as one of the most reliable barriers to PFAS.

What is emerging is not merely a compliance issue, but a risk management imperative. Beverage companies are learning that PFAS exposure can create liability through multiple pathways: product claims, branding statements, and supply chain decisions. As litigation history now shows, being below a regulatory threshold may not be enough if even trace amounts are present and undisclosed.

VSEP Vibes Newsletter

Aquaculture Wastewater

As global demand for seafood continues to rise and wild-caught fisheries face increasing pressure, land-based aquaculture has stepped into the spotlight. Among these facilities, Recirculating Aquaculture Systems (RAS) are gaining traction because they offer greater biosecurity, reduced water use, and tighter environmental control than traditional flow-through systems. But RAS comes with its own challenge: managing purge water.

Purge water is the small but concentrated wastewater stream periodically discharged from RAS systems to control nitrate accumulation, dissolved solids, and fine organic matter. While flows are low, contaminant levels are relatively high. This combination—low volume, high strength—makes purge water particularly difficult for conventional treatment systems, especially as discharge limits tighten and water reuse becomes more valuable.

Most RAS facilities begin with familiar treatment tools: settling basins, screens, clarifiers, or dissolved air flotation (DAF). These systems are effective at removing coarse, settleable solids, but they struggle with what dominates purge water—fine colloidal solids, dissolved nutrients, and phosphorus bound to sub-50-micron particles. Meeting stricter nitrogen or phosphorus limits often requires layering on chemical addition, biological denitrification, wetlands, or lagoons, all of which increase footprint, sludge production, and operational complexity.

This is where VSEP® (Vibratory Shear Enhanced Processing) changes the equation. Unlike gravity-, chemistry-, or biology-based systems, VSEP relies on a physical membrane barrier to separate contaminants by size or molecular weight. What makes it different from conventional spiral-wound membranes is how fouling is controlled. Instead of depending on crossflow velocity—which decays near the membrane surface—VSEP vibrates the membrane module 50 times per second. This

vibration generates extremely high shear directly at the membrane face, keeping solids suspended, preventing buildup, and maintaining stable flux even on waters with high TSS, organics, or scaling tendencies.

For RAS purge water, this translates into consistent removal of fine and colloidal solids, excellent phosphorus capture, and the physical concentration of nitrogen species into a much smaller reject stream. While VSEP does not biologically destroy nitrogen, it simplifies nitrogen management by reducing discharge volume, enabling reuse, or making downstream biological treatment more efficient.

Conventional treatment remains the most economical choice for high-flow, dilute effluents with relatively relaxed discharge limits. Where VSEP excels is exactly where many RAS operators struggle: low-flow, high-strength purge streams, limited land availability, and strict discharge permits. Many facilities adopt a hybrid approach. Conventional systems remove bulk solids, while VSEP treats most of the purge flow. The small VSEP concentrate can then be managed, minimizing capital risk. For decision makers facing tightening regulations, VSEP is increasingly viewed not as a luxury upgrade, but as the most direct path to predictable compliance.

V✧SEP Vibes Newsletter

Why Minnesota Has the World's Strictest Sulfate Rule — And Why It Matters for Mining

When engineers across the mining industry talk about sulfate limits, Minnesota inevitably comes up and for good reason. Minnesota's sulfate standard for certain surface waters, set at 10 mg/L, is widely regarded as the strictest sulfate rule in the world. What makes this remarkable is not just how low the limit is, but *why* it exists at all, especially when the U.S. Environmental Protection Agency (EPA) has never established a national numeric sulfate criterion.

The answer lies not in conventional aquatic toxicity, but in wild rice. Minnesota is unique in designating naturally occurring wild rice waters as a protected beneficial use under the Clean Water Act. Wild rice is not only the state grain; it is a culturally and legally protected resource for tribal nations and a defining feature of northern Minnesota's lakes and wetlands. Decades of research have shown that wild rice is acutely sensitive to sulfate, not through direct toxicity in the water column, but through sediment chemistry. Sulfate is converted by anaerobic bacteria in sediments into sulfide, which interferes with nutrient uptake by wild rice roots. The impact occurs at concentrations far below those that would affect fish or invertebrates.

Because the Clean Water Act requires states to protect designated beneficial uses, Minnesota adopted a numeric sulfate standard in 1973, long before most modern mining water challenges existed. When EPA later directed the state to enforce that long-standing rule, Minnesota had little legal flexibility. Even though EPA has no national sulfate limit, it must approve and enforce state standards that are scientifically justified and lawfully adopted. In Minnesota's case, the 10 mg/L limit met that test.

For mining engineers, the consequences are profound. Northeastern Minnesota, especially the Iron Range, has relied on mining for well over a

century. Iron ore and taconite mining are not just industries there; they are the economic backbone of entire communities. Yet mine water generated from sulfide-bearing formations naturally contains sulfate at levels that can range from hundreds to thousands of milligrams per liter. Conventional mine water treatment systems, lime neutralization, metals precipitation, settling ponds, were never designed to remove dissolved sulfate. To reach 10 mg/L requires advanced treatment: membrane systems, reverse osmosis, evaporation, crystallization, or complex hybrid systems that are energy-intensive and costly at mining scales.

The result is one of the most challenging regulatory environments mining engineers encounter anywhere in the world. Compliance is not just a matter of process optimization; it forces fundamental redesign of water management strategies, often with capital and operating costs that rival core mining infrastructure itself. Minnesota's sulfate rule is not the product of regulatory zeal, it is the outcome of law, science, and history intersecting in a very specific place. For engineers working in northeastern Minnesota, it defines the technical, economic, and environmental equation of mining in a way few other jurisdictions do.

VSEP Vibes Newsletter

Managing Reinjection Risk in Geothermal Plants

Electricity generation in geothermal plants follows the same principle as other thermal and hydraulic systems: mechanical energy is converted into electrical energy by spinning a turbine connected to a generator. High-pressure steam expands across turbine blades, causing rotation. In hydroelectric systems, the gravitational force of flowing water drive the turbine instead. With geothermal, because the heat source is the Earth itself, nothing is combusted, and there are no emissions from fuel burning or waste streams like spent nuclear fuel. This makes geothermal one of the cleanest and most reliable forms of baseload power available.

In a geothermal plant, energy production begins deep underground where high-temperature pressurized water and steam exist in tectonically active regions where it is relatively close to the surface. Production wells of about 1 to 3 miles deep bring this fluid to the surface, where a rapid pressure drop causes hot brine to flash into steam. This steam drives a turbine-generator set, converting heat into electricity. After expansion through the turbine, the steam is condensed and is ultimately routed back underground through reinjection wells to sustain reservoir pressure.

The steam for the turbine must be as dry as possible. In reality, flashing generates entrained droplets, a fine mist composed of geothermal brine. These droplets are problematic because they carry dissolved minerals, including silica, chlorides, and metal species that do not vaporize but remain in the liquid phase. To prevent scale and protect turbine integrity, geothermal plants employ droplet and mist separation systems. Cyclonic separators first remove bulk liquid by centrifugal force, while downstream demisters capture finer droplets through impingement and coalescence. Once removed from the steam, this stage is where the primary operational risk emerges. As temperature and pressure decline, silica solubility reduces, initiating polymerization into colloidal silica and eventually gel phases. Simultaneously, precipitation of carbonates

and sulfates can occur. The result is a supersaturated, particle-laden fluid. The suspended solids pose a serious threat to reinjection performance. When introduced into the formation, they can block pore throats, form filter cakes at the wellbore interface, and migrate into the reservoir where they deposit over time. This leads to declining injectivity, increased pumping pressures, and in severe cases, irreversible formation damage. Reinjection well impairment is one of the most significant lifecycle risks for geothermal assets.

Conventional clarifiers and gravity settling are largely ineffective for these systems due to the extremely small particle size and colloidal stability of silica. This is where advanced separation technologies such as VSEP offer a solution. Operating at up to 90°C, VSEP systems employ high-shear ultrafiltration to disrupt fouling layers and continuously remove suspended solids. Ultrafiltration membranes used in VSEP can effectively remove sub-micron particles, including silica polymers achieving near-complete solids removal where clarifiers cannot. By reducing the suspended solids, the treated brine becomes significantly less likely to plug pore structures or form damaging deposits within the formation. The result is a cleaner injection fluid, improved injectivity, extended well life, and reduced need for remediation interventions such as acidizing or workovers. For geothermal operators, integrating ultrafiltration into brine management represents not just a treatment step, but a strategic investment in asset reliability and long-term field performance.

VSEP Vibes Newsletter

Permitted Today, Exposed Tomorrow

For many industrial facilities, wastewater treatment is often framed as a technical hurdle with a defined solution: install the right process, meet the limits, and move forward. In reality, the more difficult challenge is not treatment itself, but determining where treated effluent can legally go—and securing permits that remain defensible over time. Discharge permitting frequently becomes the single largest source of schedule uncertainty, capital risk, and long-term operational exposure, even for well-designed projects.

At a high level, facilities fall into two categories: those with access to a publicly owned treatment works (POTW) and those without. While these pathways appear fundamentally different, both carry significant and often underestimated risk. Early assumptions about discharge options can lock projects into fragile strategies that unravel late in development or years into operation. Facilities without access to municipal sewer systems face particularly constrained choices. Surface water discharge permits can require years of study, including baseline water quality assessments, environmental impact analyses, toxicity testing, and public review. Treatment systems must perform reliably not just under average conditions, but during seasonal extremes when regulators apply the greatest scrutiny. What works during pilot testing or early operation may struggle during low-flow or runoff conditions, exposing the facility to compliance risk.

Facilities with access to a POTW often assume they have the least risky option. In practice, POTW discharge can be equally challenging. POTWs operate under their own discharge permits and are highly sensitive to industrial wastewater that could disrupt treatment processes or threaten compliance. As a result, they frequently impose local limits that are more restrictive and less predictable than federal standards. Approval is rarely purely technical and often involves negotiation over monitoring, flow management, surcharges, and enforcement terms. From a business standpoint, variability is the core challenge. POTW



requirements differ widely by municipality, regulatory history, and even management philosophy. Changes in plant leadership or compliance history can quickly alter expectations. What begins as a cooperative relationship can become constrained with little warning.

Across all discharge scenarios, the greatest risk is often not permit denial, but uncertainty. Permitting timelines are difficult to predict, and treatment design frequently proceeds before final permit conditions are known. If assumptions prove incorrect or limits tighten late in the process, facilities may face costly retrofits, delayed startups, or a complete shift in discharge strategy. Compounding this risk, permits are not static. Renewals and reopener clauses can impose stricter requirements over time, leaving systems designed for minimal compliance exposed.

For executives, the takeaway is clear: discharge permitting is a strategic business risk, not a regulatory formality. Whether discharging to surface waters or a POTW, success depends on conservative assumptions, strong data, and treatment strategies that provide margin and flexibility. In many cases, the greatest threat is not failing to obtain a permit, but discovering years later that a permitted discharge is far less secure than it once appeared.

VSEP Vibes Newsletter

Problems with Excess Manure Spreading

For generations, livestock manure has been valued as a natural fertilizer—returning nutrients to the soil and closing the loop between animals and crops. On many modern livestock farms, manure slurries from barn washing and animal housing are land-applied to nearby fields, providing nitrogen, phosphorus, organic matter, and other beneficial elements. When managed carefully, this practice can support productive agriculture and reduce the need for commercial fertilizers. However, when manure is applied too frequently, in excessive amounts, or at the wrong time of year, the benefits can quickly turn into serious environmental and community challenges.

One of the most visible impacts of excessive manure application is nutrient runoff. When soils are saturated or frozen, or when rainfall follows spreading events, nutrients, especially phosphorus, can move with surface water into nearby ditches, creeks, and lakes. Once there, these nutrients fuel algal blooms that cloud the water, reduce oxygen levels, and harm aquatic life. In some cases, harmful algal blooms can produce toxins that make water unsafe for recreation, livestock, or even drinking water supplies. What began as a nutrient recycling practice on the farm can ultimately degrade water quality far downstream.

Excess nitrogen from manure, typically in the form of nitrate, poses another significant risk. When more nitrogen is applied than crops can absorb, nitrates can leach downward through the soil profile and into groundwater aquifers. Private drinking water wells in agricultural areas are particularly vulnerable. Elevated nitrate levels in drinking water are a health concern, especially for infants, where they can cause serious illness. For rural families who rely on wells, over-application of manure can translate into costly water treatment or the need to find alternative water sources.

Unlike nitrogen, which can be lost to the air or leached downward, phosphorus tends to remain in the soil. Over time, repeated manure applications can lead to phosphorus levels far above what crops actually need. Once soils become saturated, any additional application increases the risk of phosphorus loss to surface water. Even if manure applications are reduced later, legacy phosphorus already in the soil can continue contributing to runoff for years or even decades. This makes over-application particularly difficult and expensive to correct.

Ironically, too much manure can also harm the soil it's meant to improve. Excess nutrients can create imbalances, interfere with micronutrient uptake, and increase salt levels in the soil. Crop yields may stagnate or decline, despite high nutrient inputs. Manure applied to fields without regard to crop nutrient needs can lead to nitrogen losses as ammonia gas, and contributing to odors, air quality issues. Excessive manure application can strain relationships between farms and surrounding communities. Odors, visible runoff, and concerns about water quality often draw public attention and increase regulatory scrutiny. In many regions, this has led to tighter nutrient management requirements and higher compliance costs for farmers.

V✧SEP Vibes Newsletter

The Radium Craze and Lessons Learned

In the early 1920s, radium symbolized everything people loved about the modern age. Recently discovered by Marie and Pierre Curie and mysteriously glowing, it seemed to embody scientific progress itself. Doctors, and entrepreneurs promoted radium as a substance that could restore vitality, cure disease, and slow aging. It was added to drinking waters, skin creams, toothpastes, and medical treatments, often containing radium-226 or radium-228. To consumers, radium felt like health harnessed by science.

The enthusiasm was fueled by real discoveries. Radiation had shown promise in destroying cancer cells, and early therapeutic uses suggested benefits—at least in controlled settings. But the leap from medical application to consumer product happened far faster than scientists understood the risks. Products like Radithor, a radium-infused tonic drink, promised energy and youth in a bottle. Cosmetics boasted a "healthy glow," while ointments claimed to heal from the outside in. The idea that a little radiation might stimulate the body rather than harm it seemed plausible, even progressive.

The danger, however, worked slowly. Radium behaves like calcium in the body, lodging itself in bones where it continues emitting radiation for years. Illnesses developed over time: bone fractures, jaw necrosis, anemia, and cancers. Eben Byers, a wealthy industrialist who drank Radithor daily, became one of the most famous victims; by his death in 1932, his bones were literally disintegrating. Even more tragic were the *Radium Girls*, young factory workers who painted luminous watch dials. Encouraged to shape their brushes with their lips, they unknowingly ingested radium every day. Many suffered devastating illnesses and early deaths. Their lawsuits eventually forced changes in industrial safety regulations and worker protections, but at enormous human cost.

By the mid-1930s, the radium craze collapsed. Regulation replaced enthusiasm, and radium transformed from wonder cure to warning label.

Looking back, it seems astonishing that such a dangerous substance was once so casually consumed. Yet the story is not one of foolishness so much as one of timing: scientific innovation outpaced toxicology, regulation, and long-term health studies.

That imbalance persists today. We no longer ingest radioactive tonics, but modern life is steeped in chemicals whose long-term effects are still emerging. PFAS, once prized for non-stick cookware and stain-resistant fabrics, now raise concerns about cancer, immune suppression, and hormone disruption. Microplastics, byproducts of modern convenience, are found in water, air, and even human tissue. Pharmaceuticals and personal care chemicals move through wastewater systems and reenter the environment largely unchanged.

Like radium a century ago, these substances were widely adopted because they worked. Their benefits were immediate and obvious; their harms subtle, cumulative, and easy to miss. The lesson of the radium era is not to distrust science, but to respect its limits. Absence of immediate harm is not proof of safety. Radium's faint glow once promised health and progress. Instead, it left a legacy of caution. As we confront today's emerging pollutants, that history reminds us to pair innovation with humility and to ask hard questions before time answers them for us.

VSEP Vibes Newsletter

Bordo Poniente: A Closed Landfill, an Open Leachate Problem

When Mexico City officially closed the Bordo Poniente landfill in December 2011, it marked the end of active disposal at what was, for decades, one of the largest municipal landfills in the world. Over more than twenty-five years of operation, Bordo Poniente received well over 70 million tons of municipal solid waste, stacked across hundreds of hectares in the former Lake Texcoco basin. Closing the gates, however, did not close the engineering story.

Like all mega-landfills of its era, Bordo Poniente carries a post-closure life measured not in years, but in decades. The waste mass continues to generate methane and leachate, both of which must be actively managed far into the future. While methane capture has been embraced—today the landfill gas system produces electricity fed to the grid—the same cannot be said for leachate treatment. Since closure, Bordo Poniente has never implemented a permanent, on-site leachate treatment system. Instead, leachate is collected, pumped, and stored in lined lagoons, then periodically hauled off-site by tanker trucks for external treatment. This approach is operationally straightforward but economically and environmentally expensive. Transporting high-strength, saline landfill leachate over long distances adds recurring cost, increases emissions, and leaves the city dependent on external treatment capacity that was never designed for sustained post-closure flows.

The scale of the challenge is not trivial. A landfill of Bordo Poniente's size is expected to generate millions of cubic meters of leachate over its post-closure life, with peak volumes driven by seasonal rainfall and the site's sensitive hydrology. Stored leachate basins, that are so large they can be seen from outer space, represent an ongoing risk in the Valley of Mexico, where groundwater protection and flood control are already critical concerns. Containment works, no matter how well engineered, are only as reliable as the systems and budgets that maintain them year after year.

Mexico City VSEP Landfill Installation

What makes this situation particularly notable to engineers is that alternatives were demonstrated—successfully—before the landfill even closed. Vibratory Shear Enhanced Process (VSEP) membrane technology was pilot-tested at full scale at Bordo Poniente prior to closure, showing that high-fouling landfill leachate could be reliably treated on site. VSEP's high shear membrane operation is well suited to aged leachate with elevated COD, ammonia, and dissolved solids, offering high recovery at a fraction of the lifecycle cost of truck-and-treat paradigms.

Even more compelling is the opportunity missed by separating leachate management from energy recovery. Bordo Poniente already captures methane for electricity generation. That same energy resource could be redirected—or supplemented—to power thermal evaporation of VSEP reject, enabling a true zero-liquid-discharge (ZLD) solution. Instead of exporting a liability, the site could internally manage leachate through membrane concentration followed by energy-driven volume reduction, closing the water balance at the landfill itself. Fifteen years after closure, Bordo Poniente remains a reminder that closing a landfill is not the same as finishing the engineering. The waste will be there for decades. The leachate will continue to form. The question is whether future management continues to rely on costly off-site transport or finally adopts integrated, on-site solutions that were already proven possible.

VSEP Vibes Newsletter

Drought and Denial, are we Repeating the Past?

We often look back at ancient civilizations with a sense of superiority. After all, we command satellites, artificial intelligence, and global communication networks, all tools unimaginable to the engineers of the past. Yet scattered across history are the remains of societies that once felt just as enduring as ours and demonstrated incredible engineering and intelligence. The Moche of Peru, the Maya of Mesoamerica, the Akkadians of Mesopotamia, each stood at the height of cultural and technological achievement in their time. And each was humbled by the environment.

The Moche carved a thriving advanced civilization out of Peru's arid coastal valleys nearly 1,500 years ago. Their irrigation canals transformed the desert into fertile farmland, supporting cities, artistry, and complex social systems. But when intense El Niño rains flooded their carefully engineered networks, followed by prolonged drought, the system began to fail. Food production faltered. Social order collapsed. Eventually, their great centers were abandoned, leaving only pyramids of mud brick.

Far to the north, the Maya built soaring temples and devised advanced calendars and mathematics deep within tropical forests without calculators or computers. Their cities depended heavily on rainfall, stored in engineered reservoirs and managed through careful planning. Then came decades-long droughts. Forests had already been cleared extensively, making the land vulnerable. Water became scarce, crops failed, and rival city-states turned on one another. By the 9th century, many of their great urban centers stood empty all precipitated by drought and lack of water resources.

These were not primitive societies undone by ignorance. They were intelligent sophisticated societies with incredible engineering and mathematics skills. They engineered canals, tracked celestial movements, and built monumental cities without modern machinery or tools. Yet they shared with us a vulnerability: dependence on environmental stability. When that stability disappeared, their complexity became fragility.

Climate variability is not new. Droughts, floods, and shifting weather patterns have shaped human history long before industrialization. A prolonged drought today does not affect just one valley or region, it can ripple through global food systems, economies, and political structures. History does not repeat exactly, but it echoes. The ruins of past civilizations are not merely relics; they are warnings carved in stone. They remind us that resilience requires foresight, planning, and respect for the systems that sustain us. What should be our advantage is knowledge of science, of history, and of the consequences of inaction.

Civilizations have risen during favorable conditions and fallen when those conditions shifted. We do not control these forces as much as we often believe. Recognizing that reality and planning for disruptions like drought, water scarcity, and extreme weather is not something we should ignore or history will repeat.

VSEP Vibes Newsletter

Metal Finishing - One of Industry's Toughest Problems

In just the last 28 days, more than 2,300 people searched for solutions to metal-finishing wastewater on our website. That level of sustained interest tells a clear story: despite decades of experience, capital investment, and regulatory oversight, this problem is far from solved. Metal finishing wastewater is uniquely difficult because it is rarely simple or consistent. Unlike many industrial effluents, it often contains a constantly changing mix of dissolved heavy metals, chelating agents, surfactants, oils, extreme pH, and high dissolved solids. Job shops and multi-line operations may produce radically different wastewater profiles depending on what process is running that day, or even that hour. Systems designed for steady-state operation struggle in environments defined by variability.

Compounding that challenge is the fact that many treatment systems in use today were designed for a regulatory landscape that no longer exists. Traditional precipitation, clarification, and sludge-based systems worked reasonably well when discharge limits were higher and sludge disposal was inexpensive. Today, tighter discharge permits, rising disposal costs, and increased scrutiny of nutrients, boron, fluorides, PFAS, and total dissolved solids have pushed these legacy systems well beyond their intended operating envelope.

One of the most persistent and least understood obstacles is metal chelation. Modern plating and finishing chemistries intentionally keep metals in solution to improve process control and surface quality. Those same chelants prevent metals from precipitating, bypass ion exchange, and cause erratic compliance failures. Many facilities only discover this problem after years of escalating chemical usage and inconsistent effluent results.

The situation is further complicated by growing pressure to reduce water consumption altogether. Zero-liquid-discharge mandates, reuse initiatives, and restrictions on sewer access are forcing metal finishers to concentrate and recycle wastewater, something traditional treatment systems were never designed to do efficiently. What once was a "treat and discharge" problem has become a "separate, concentrate, and reuse" challenge. Underlying all of this is a simple organizational reality: wastewater is not the core business of metal finishers. Systems are often under-sized, over-patched, and operated reactively. Problems are addressed when they become urgent, not when they start. That is why so many engineers, plant managers, and environmental professionals continue searching for better answers.

VSEP's unique high-shear membrane technology is specifically suited for difficult, high-solids, high-fouling wastewaters. By continuously cleaning the membrane surface through vibration, rather than relying on high crossflow velocity, VSEP concentrates dissolved metals, chelates, and salts without the plugging, scaling, or chemical instability that limit conventional membranes. For metal finishers facing tightening regulations, rising disposal costs, or water-reuse mandates, VSEP offers a robust, proven path forward: fewer chemicals, less sludge, reliable compliance, and real progress toward water sustainability. The search traffic tells the story, industry is looking for solutions. VSEP delivers one.

VSEP Vibes Newsletter

Sewage, Gravity, and the Border

Stand at the U.S.–Mexico border near San Diego and one thing becomes clear: Tijuana is uphill. Gravity lies at the heart of the ongoing Tijuana sewage crisis. The Tijuana River watershed begins in Mexico, runs through the rapidly growing city of Tijuana, crosses the international border, and then flows directly through U.S. communities before emptying into the Pacific Ocean near Imperial Beach. When everything works as designed, sewage generated in Tijuana is collected, pumped, and treated on the Mexican side or routed to ocean outfalls. But when the system fails, and it does so frequently, the wastewater doesn't stop at the border. It runs downhill. Tijuana's sewage system was built decades ago for a much smaller population. As the city expanded, pipes, pump stations, and treatment plants became undersized and increasingly prone to failure. When a pump station goes offline or a pipe breaks, sewage has to go somewhere. Often, it escapes through manholes, ruptured lines, or emergency overflows. From there, it follows the natural terrain.

Tijuana is carved by steep canyons: Los Laureles, Goat Canyon, and Smuggler's Gulch that act like funnels. Once sewage enters these channels, there is no mechanism to stop it. The canyons cross the border without regard for politics or treaties, delivering untreated wastewater directly into the United States. Concentrated sewage trickles or pours north day after day, undiluted and highly contaminated. The U.S. couldn't ignore what was arriving on its doorstep Once sewage crosses into the United States, it becomes a public-health emergency on U.S. soil. Raw sewage spreading across the Tijuana River Valley contaminates land, water, and air. It produces hydrogen sulfide gas. It closes beaches. It triggers environmental laws requiring action, regardless of where the pollution originated.

Faced with this reality, the U.S. made a pragmatic decision decades ago: intercept the sewage before it spreads further inland. To protect U.S. communities, many people don't know that federal agencies installed canyon collectors and interceptors at the border, concrete channels and pipes designed to capture sewage flowing downhill from Mexico. The captured wastewater is then diverted to the South Bay International Wastewater Treatment Plant, a U.S.-owned facility originally built in the 1990s solely to treat sewage from Mexico.

The purpose was not to solve Tijuana's sewage problem. It was to contain the damage. These systems were intended as emergency safeguards, a way to manage occasional failures. But as Tijuana's infrastructure continued to degrade and the city continued to grow, emergency conditions became routine. What was meant to be a backstop slowly turned into a primary line of defense. The U.S. treatment plant handle large volumes of Mexican sewage when failures occur. And that has created an unintended consequence: reliance. Instead of serving as a temporary safety net while Mexico upgraded its systems, the U.S. infrastructure increasingly functions as the default solution when things go wrong in Tijuana. The more capacity the U.S. builds to protect itself, the more the system absorbs upstream failures without addressing their root cause.

VSEP Vibes Newsletter

The U.S. collection systems and treatment plant built in the 1990s were never designed to handle today's reality. They were built as emergency safeguards meant to capture occasional sewage overflows when Tijuana's system failed, not to manage constant, high-volume failures. Over time, Tijuana's population grew far beyond what its aging infrastructure could support, and breakdowns became routine rather than rare. When pumps fail or pipes rupture, sewage enters multiple canyons at once, often overwhelming the limited capacity of U.S. interceptors. Some flows bypass collection points entirely; others exceed what the treatment plant can process. The result is that even with interception in place, polluted water still reaches the river and the ocean forcing beach closure. What was intended as a temporary backstop has become a permanent line of defense, one that reduces harm, but cannot fully contain a problem that originates uphill and continues to grow.

The choice is grim but clear: treat the sewage or allow it to contaminate American communities. Doing nothing is not an option. There are treaties governing all of this. International agreements clearly state that each country is responsible for pollution originating within its borders. Meanwhile, sewage flows downhill every day. Faced with an immediate threat to public health, the U.S. responds with interception and treatment, because it cannot legally or ethically ignore it.

Thank you for subscribing to our newsletter. I hope you find it informational and fun. You are one of 3,600 professionals and industry stakeholders who receive this newsletter each month.

About the newsletter author:

Greg Johnson is CEO of New Logic Research and is responsible for the development of VSEP technology since 1992. gjohnson@vsep.com

New Logic Research, Inc.
2527 Aviation Way
Minden, NV 89423 USA
775-783-7600
www.vsep.com
info@vsep.com

June 2026 Newsletter Edition